

Technical References – Targets only, without tolerances mentioned

	Whiteness	Opacity	Moisture	Bendtsen Roughness	Thickness	Bulk
	CIE	%	%	ml/min	µm	µm/g/m ²
	ISO 11475	ISO 2471	ISO 287	ISO 8791/2	ISO 534	—
75 g/m² Eco-Logical	169	93,0	4,0	180	105	1,40
80 g/m² Universal	169	95,0	4,0	120	110	1,38
90 g/m² Inkjet	169	96,0	4,0	100	116	1,29
100 g/m² Presentation	169	97,0	4,0	100	120	1,20
120 g/m² ColourDoc	169	98,0	4,0	50	128	1,07
160 g/m² Office Card	169	97,5 (minimum)	5,0	50	170	1,06

Additional Information about grupo Portucel Soporcel Mills and Products:

grupo Portucel Soporcel mills are chain-of-custody certified by the Smartwood Program of the Rainforest Alliance in accordance with FSC-STD-40-004 (SW-COC-1783 for Soporcel and SW-COC-1829 for Portucel).

In accordance with the requirements of ISO 9706 standard - Archival life over 200 years

Elemental Chlorine Free (ECF)

Quality Standard ISO 9001

Environmental Standard ISO 14001

Occupational Health and Safety Standard OHSAS 18001